


JAS-FH08
IP NVR



Main Features

Up to 9-ch IP camera inputs

H.265+/H.265/H.264+/H.264 video formats

1 HDMI and 1 VGA

1 SATA up to 8Tb

1920 × 1080/60Hz

Up to 5MP (2592 × 1944)

DC12V/2A



SYSTEM	
CPU	ARM Cortex A7 Processor
OS	Embedded LINUX
Video	
IP Input	9CH (2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)
Output	1 VGA, 1 HD
Audio	
Input	/
Output	1 Port 3.5mm(Linear, 1kΩ)
Bitrate	64kbps
Audio Compression	G711u, G711a, G726
Alarm	
Input	/
Output	/
Motion Detection	9 Ch, 396 (22 × 18) Zones
Event	Recording, Email, FTP, Snapshot, Buzzer и Screen Tips
Display	
HD Input	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HD Output	/
VGA	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Screen Division	9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP
Digital Zoom	Yes
OSD	Signature, Time, Recording, Motion detection
Recording	
Video compression	H265/H264/H265+/H264+
Resolution	5MP(2592×1944),4MP(2688×1520),3MP(2048×1536),1080P(1920×1080) 960P(1280x960), 720P(1280×720),D1 (720×576/720×480)
Recording Quality	PAL:5MP@9×25fp,4MP@9×25fp,3MP@9×25fp,1080P@9×25fp,960P@9×25fp,720P@9×25fp, D1@9×25fp; NTSC: 5MP@9×30fp,4MP@9×30fp,3MP@9×30fp,1080P@9×30fp,960P@9×30fp, 720P@9×30fp, D1@9×30fp
Recording Mode	Manual, Timer, Motion Detection

Playback	
Local	1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
Decoding	4CH 1080P@20fps
Remote Playback	Yes
Searching	Yes, by channel, manual, by time, by date, by motion detection
Backup	USB Device/Network
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Incoming Bandwidth	60MB
Network Protocol	TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
Onvif	Yes, 2.4
Web Browser	IE8-11, Google Chrome, Firefox
CMS	Windows 7/ Windows 8/Windows 10
Cloud Support(P2P)	Yes, Bitvision
Smart Phone	iPhone, iPad, Android, Android Pad
HDD	
SATA	1 SATA Interface
Capacity	Up to 8TB
eSATA	/
General	
Languages	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland
USB	2 x USB 2.0
Rs485	/
Power Consumption	DC12V±10%, 2 A
Operating Conditions	-10°C ~ +55°C RH95% Max
Dimensions	260*215*43 mm
Weight	2,0 kg