

JAS-PT10G136SS500**5.0 MP CMOS Network Camera**

Main Features

1/2.8" SONY Starvis Back-illuminated CMOS sensor

5.0 megapixel

4.6-165mm motorized focal lens

UP to 240 m IR range

Dual stream

WDR (Wide Dynamic Range)

3D DNR

PTZ

IP 66, IK 10



Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	5MP
Effective pixels	2616 (H) x 1964 (V)
Video Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Shutter Speed	PAL 1/25-1/10000 s; NTSC 1/25-1/10000 s
Min. Illumination	0.01 Lux
S/N Ratio	≥52dB
Movement Range	Pan: 360°, Tilt: 0° to 90°
Zoom	36x
Rotation Speed	100°/s
Preset Points	22
Lens	
lens	4.6-165mm
Angle	64° - 1,7°
Focus	Auto
Type	Motorized
IR Cut	
IR Led	42 x 10PCS IR LEDS + 5 PCS LED Laser
IR Range	Up to 240 m
Condition	Auto
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Yes, 2.4
P2P	Yes, with QR-Code
Video delay	0.3S
Main Stream 1	2560*1920@20fps
Main Stream 2	2560*1440@25fp
Main Stream 3	2304*1296@25fps
Main Stream 4	1920*1080@25fps
Main Stream 5	1280*720@25fps

Main Stream 6	640*512@25fps
Sub Stream 1	800*448@25fps
Sub Stream 2	704*576@25fps
Sub Stream 3	640*360@25fps
Sub Stream 4	352*288@25fps
Features	
Day/Night	Color/ IR Cut
Image Settings	Saturation / Brightness / Contrast / Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control), Video Tampering
Corridor Format	Yes
Defog Mode	Yes
ROI	Yes, 3 zones
WDR	120dB
BLS	Yes
HDR	Yes
Motion Detection	Yes
Masks	Yes, 3 zones
Recoding Mode	NVR/CMS/Web
Languages	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland
Interface	
Audio	/
SD Card	/
RS 485	/
General	
Frame	Metal ,IP67, Ik10
Operating Conditions	-30°C ~ +60°C RH95% Max
Storege Conditions	-20°C ~ +60°C RH95% Max
Lightning Protection	6000V
Power Consumption	DC12V±10%, 4A
Dimensions	330(W) x 330(H) x 520(D)mm
Weight	13,7 kg